



# 10 BAR

Acc. to BS 4504


## WELD NECK FLANGES SLIP-ON FLANGES BLIND FLANGES



**WELD NECK RF**



**SLIP-ON RF**



**BLIND RF**

Nominal Bore	Outside Diameter <i>D</i>	Pitch Circle Diameter <i>K</i>	Diameter of Bolts	No. of Holes	Approximate Weight (Kgs)	
					SLIP ON	WELD NECK
15	95	65	M12	4	0.675	0.648
20	105	75	M12	4	0.947	0.952
25	115	85	M12	4	1.14	1.14
32	140	100	M16	4	1.66	1.69
40	150	110	M16	4	1.89	1.86
50	165	125	M16	4	2.51	2.53
65	185	145	M16	4	3.00	3.06
80	200	160	M16	4	3.79	3.70
100	220	180	M16	8	4.20	4.62
125	250	210	M16	8	5.71	6.30
150	285	240	M20	8	6.72	7.75
200	340	295	M20	8	9.50	11.30
250	395	350	M20	12	12.50	14.70
300	445	400	M20	12	14.40	17.60
350	505	460	M20	16	20.60	23.60
400	565	515	M24	16	27.90	28.60
450	615	565	M24	20	35.00	34.00
500	670	620	M24	20	41.10	38.10
600	780	725	M27	20		
700	895	840	M27	24		
800	1015	950	M30	24		
900	1115	1050	M30	28		
1000	1230	1160	M33	28		

\*All dimensions in mm.

\* All weights indicated are approximate.