



25 BAR

Acc. to BS 4504


WELD NECK FLANGES SLIP-ON FLANGES BLIND FLANGES



WELD NECK RF



SLIP-ON RF



BLIND RF

Nominal Bore	Outside Diameter <i>D</i>	Pitch Circle Diameter <i>K</i>	Diameter of Bolts	No. of Holes	Approximate Weight (Kgs)	
					SLIP ON	WELD NECK
15	95	65	M12	4	0.81	0.746
20	105	75	M12	4	1.24	1.06
25	115	85	M12	4	1.38	1.29
32	140	100	M16	4	2.03	1.88
40	150	110	M16	4	2.35	2.34
50	165	125	M16	4	3.20	2.82
65	185	145	M16	8	4.29	3.74
80	200	160	M16	8	5.88	4.75
100	235	190	M20	8	7.54	6.52
125	270	220	M24	8	10.8	9.07
150	300	250	M24	8	14.5	11.8
200	360	310	M24	12	22.3	17.0
250	425	370	M27	12	33.5	24.4
300	485	430	M27	16	46.3	31.2
350	555	490	M30	16	68.0	47.2
400	620	550	M33	16	89.7	61.7
450	670	600	M33	20	115	72.0
500	730	660	M33	20	138	89.6
600	845	770	M36	20		104
700	960	875	M39	24		136
800	1085	990	M45	24		186
900	1185	1090	M45	28		236
1000	1320	1210	M52	28		307

*All dimensions in mm.

* All weights indicated are approximate.